

Printing date 18.07.2013 Version number 14 Revision: 18.07.2013

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- Product identifier
- Trade name: UK PLANET FIRE RATED FOAM B1
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance / the preparation Construction chemicals

Assembly foam

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UK PLANET LTD

Unit 1, Holdom Avenue, Saxon Park, Milton Keynes, MK1 1QU, United Kingdom

www.ukplanet.co.uk

- · Further information obtainable from: info@ukplanet.co.uk
- · Emergency telephone number: 112

SECTION 2: Hazards identification

- · Classification of the substance or mixture
- Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20-40-48/20: Harmful by inhalation. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Xn; Harmful

R42/43: May cause sensitisation by inhalation and skin contact.

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

F+; Extremely flammable

R12: Extremely flammable.

Information concerning particular hazards for human and environment:

Combustible gas, more heavy from air; can crowd at surfaces and in lower parties of rooms. Foam is easily to glue to the skin and other surfaces.

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. Warning! Pressurized container.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 2)



Printing date 18.07.2013 Version number 14 Revision: 18.07.2013

Trade name: UK PLANET FIRE RATED FOAM B1

(Contd. of page 1)

· Code letter and hazard designation of product:





Xn Harmful

F+ Extremely flammable

· Hazard-determining components of labelling:

polymethylene polyphenyl polyisocyanate, isomers and homologues

· Risk phrases:

Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

Limited evidence of a carcinogenic effect.

42/43 May cause sensitisation by inhalation and skin contact.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Extremely flammable. 12

Safety phrases:

Do not breathe gas.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where 45

51 Use only in well-ventilated areas.

In case of accident by inhalation: remove casualty to fresh air and keep at rest. 63

Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

- -Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- -Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- -This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Keep away from sources of ignition - No smoking.

Do not spray on a naked flame or incandescent material.

Keep out of the reach of children.

- Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 9016-87-9	polymethylene polyphenyl polyisocyanate, isomers and homologues Xn R20-40-48/20; Xn R42/43; Xi R36/37/38 Carc. Cat. 3 ♣ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ♠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	30.0 - 60.0%
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate Xn R22 Acute Tox. 4, H302	< 25.0%

(Contd. on page 3)



Printing date 18.07.2013 Version number 14 Revision: 18.07.2013

Trade name: UK PLANET FIRE RATED FOAM B1

		(Contd. of page 2)
CAS: 74-98-6	propane	< 15.0%
EINECS: 200-827-9	A F+ R12	
	Flam. Gas 1, H220; 🔷 Press. Gas, H280	- 1
CAS: 106-97-8	butane	< 15.0%
EINECS: 203-448-7	A F+ R12	
	♦ Flam. Gas 1, H220; ♦ Press. Gas, H280	-
CAS: 75-28-5	isobutane	< 15.0%
EINECS: 200-857-2	A F+ R12	
	♦ Flam. Gas 1, H220; ♦ Press. Gas, H280	-
CAS: 115-10-6	dimethyl ether	< 10.0%
EINECS: 204-065-8	▶ F+ R12	
	♦ Flam. Gas 1, H220; ♦ Press. Gas, H280	- 1

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Remove uncured foam using a piece of cloth and an unagressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Rinse out mouth and then drink plenty of water.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:

Carbon dioxide

Fire-extinguishing powder

Foam

Water haze

Use fire extinguishing methods suitable to surrounding conditions.

Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

GE



Printing date 18.07.2013 Version number 14 Revision: 18.07.2013

Trade name: UK PLANET FIRE RATED FOAM B1

(Contd. of page 3)

SECTION 6: Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Wear protective clothing.

Do not breathe gas/fumes/vapour/spray.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents, e.g. acetone, alcohol. Remove cured foam mechanically.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

· Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· Conditions for safe storage, including any incompatibilities

· Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility:

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from oxidizing agents.

Store away from foodstuffs.

· Further information about storage conditions:

Store in vertical position in closed original containers.

Protect from frost.

Store at temperature from + 5 $^{\circ}$ C to + 30 $^{\circ}$ C.

Store under lock and key and out of the reach of children.

Keep container tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

GB.



Printing date 18.07.2013 Version number 14 Revision: 18.07.2013

Trade name: UK PLANET FIRE RATED FOAM B1

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· Control parameters

Ingredients with limit values that require monitoring at the workplace:

9016-87-9 polymethylene polyphenyl polyisocyanate, isomers and homologues

WEL | Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Polyethylene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection:



Tightly sealed goggles

· Body protection: Protective work clothing





Printing date 18.07.2013 Version number 14 Revision: 18.07.2013

Trade name: UK PLANET FIRE RATED FOAM B1

(Contd. of page 5)

|--|

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aeroso

Rapidly curing foam dispensed by gaseous propellant from an

aerosol container.

Colour: Rose

· **Odour:** Characteristic

· **pH-value:** Not determined

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

· Flash point: < 0 °C (propelant)

· **Self-igniting:** > +350 °C (propelant)

· Danger of explosion: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower: +/- 1.5 Vol % **Upper:** +/- 11 Vol %

• **Vapour pressure:** >500 kPa (in the container)

< 1*10-5 mmHg w 25 °C (MDI)

• **Density at 20 °C:** ≤1.3 (PMDI) g/cm³

· Solubility in / Miscibility with

water: Insoluble. reacts with water

· Partition coefficient (n-octanol/water): Not determined

• Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials:

Strongly reacts with water and other substances containing an active hydrogen atom

· Hazardous decomposition products: No dangerous decomposition products known.

GB





Printing date 18.07.2013 Version number 14 Revision: 18.07.2013

Trade name: UK PLANET FIRE RATED FOAM B1

(Contd. of page 6)

SECTION 11: Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:			
13674-84-	13674-84-5 tris(2-chlorisopropyl)-phosphate		
Oral	LD50	> 2000 mg/kg (rat)	
Dermal	LD50	> 2000 mg/kg (rat)	
Inhalative	LD50	> 0.5 mg/l (rat)	
101-68-8 4,4'-methylenediphenyl diisocyanate		lenediphenyl diisocyanate	
Oral	LD50	9200 mg/kg (rat)	
Inhalative	LC50/4 h	178 mg/l (rat)	

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

SECTION 12: Ecological information

- · Toxicity
- · Aquatic toxicity:

13674-84-5 tris(2-chlorisopropyl)-phosphate

EC50 47 mg/l (96h) (algae)

- · Persistence and degradability Not biodegradable
- · Behaviour in environmental systems:
- · Bioaccumulative potential Does not accumulate in organisms
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
07 02 08*	other still bottoms and reaction residues
07 02 13	waste plastic

(Contd. on page 8)





Printing date 18.07.2013 Version number 14 Revision: 18.07.2013

Trade name: UK PLANET FIRE RATED FOAM B1

(Contd. of page 7)

15 01 05 composite packaging

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	ation
UN-Number ADR, IMDG, IATA	1950
UN proper shipping name ADR, IMDG, IATA	AEROSOLS
Transport hazard class(es)	
ADR, IMDG, IATA Class Label	2 Gases. 2.1
Packing group ADR, IMDG, IATA	Void
Environmental hazards: Marine pollutant:	No
Special precautions for user Danger code (Kemler): EMS Number:	Warning: Gases. - F-D,S-U
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	I II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Transport category Remarks:	LQ2 2 Exemption from ADR provisions by LQ principal (rule 3.4 Inner packaging, max. 1 liter in capacity; outer packagen max. gross weight of 30kg Inner packaging, max. 1 liter in capacity, based common ground and covered with shrink film – max. groweight of 20kg.

SECTION 15: Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 9)



Printing date 18.07.2013 Version number 14 Revision: 18.07.2013

Trade name: UK PLANET FIRE RATED FOAM B1

		(Contd. of page 8)
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H351	Suspected of causing cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	
R12	Extremely flammable.	
R20	Harmful by inhalation.	
R22	Harmful if swallowed.	
	Irritating to eyes, respiratory system and skin.	
R40	Limited evidence of a carcinogenic effect.	
R42/43	May cause sensitisation by inhalation and skin contact.	
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhal	ation.

Recommended restriction of use

Sealing and mounting of construction elements.

Mounting of doors or windows cannot be performed without the use of mechanical connectors. Before use, naturally bring the can up to room temperature. Shake well the container. Screw the straw on or screw can onto the gun valve. Working position is the "bottom up". Control the spray volume adjusting the pressing force applied on the feeding nozzle or gun handle. After release from container the foam increases its volume. Use special cleaner to remove excess of uncured foam (cured foam can be removed mechanically only). After full cure protect the foam against UV radiation. Under lower temperatures the foam extends and hardens slower. The information stated above is based on current knowledge and applies to the product in the form in which it is used. Data concerning this product is presented in order to fulfill safety requirements and not to guarantee its specific properties

In cases when application conditions are not subject to manufacturer's control, the responsibility for safe product use and obeying law regulations in particular, lies on the user's side. Information in the appropriate technical data sheet of product.

Department issuing MSDS: Product safety department.

* Data compared to the previous version altered.

- 1) So far unclassified substance CAS: 13674-84-5 added in pt 3; MDI reclassification
- 2) Change in classification of compound in pt 2
- 3) Change in storage temperature in pt 7
- 4) Pts 11 & 12 enhanced by data for new substances
- 5) information about collection of empty containers in 13 pt have been removed.
- 6) Change in pt 15 resulting from compound reclassification

Update date: 07.05.2010

GB